

2

1

B

B

A

A

#2 X 1/8" LG SCREW INSULATOR
(McMASTER-CARR # 91145A110 OR EQUIV.)

RING TERMINAL

SEE NOTE 1

(2) #2 CAP SCREW

(2) #2 LOCKWASHER

(2) #2 FLATWASHER

(-)

SHORTING SCREW, REMOVE
BEFORE USING DIODE

(+)

SEE NOTE 1

INDIUM FOIL
.010" THICK

NOTES:

- 1. ASSUMES COLD PLATE IS PART OF THE ELECTRICAL CIRCUIT (+).
IF NOT, A NON-CONDUCTING SCREW MUST BE USED AT THIS LOCATION.
- 2. ALL MOUNTING HARDWARE & RING TERMINAL SUPPLIED BY CUSTOMER.

NORTHROP GRUMMAN

Cutting Edge Optonics

A PACKAGE G.B. MOUNTING

DIMENSIONS ARE IN INCHES AND INCLUDE
CHEMICALLY APPLIED OR PLATED FINISHES
GENERAL TOLERANCES UNLESS NOTED:
X.X = ±.1 X.XXX = ±.005
X.XX = ±.01 ANGLES = ±.5°

SIZE	A	MOUNTING-A-PACK-GOLDEN-BULLET-F5
SCALE:	NONE	SHEET 1 OF 1

